

GL612/GL622

Applications

General Construction

- Leveling concrete forms and footers
- Vertical alignment such as wall, columns and form alignment

Machine Guidance Compatible

- Dual slope grading and steep slope excavating
- Slope work for sports fields, tennis courts, driveways, parking garages, ramps

Pipe and Drainage Installations

- Over-the-Top sewer and drainage pipe installations
- Trenching and drainage



Easy-To-Use, Full Featured Automatic Grade Lasers



The Spectra Precision® GL612 single grade and GL622 dual grade lasers are automatic self-leveling, rugged and cost-effective. An intuitive keypad and graphic display make all grade and alignment functions easy to use and greatly reduces setup time and increases productivity. A matching remote control also simplifies all level, grade, and vertical alignment setup tasks.



Key Features

Ultimate Control of X/Y Axes

- Fully automatic up to $\pm 25\%$ grade on X/Y axes
- Automatic Axis Features (X Axis - only GL622)
 - High Precision Axis Alignment (only GL622)
 - Simplified Grade Match: measures and displays the existing grade over unknown ground
 - Complete PlaneLok: automatically locks on the laser beam to an existing elevation
- Alignment range for both axes is $\pm 40^\circ$
- Fully automatic vertical leveling

Built for Today's Jobs

- Withstands a 1 m (3 ft) drop onto concrete
- Long operating range - 800 m (2,600 ft) diameter
- Intuitive keypad and graphic display
- Password secured
- Mask mode
- Various power options
- Automatic temperature compensation
- Electronic leveling vibration filter

User Benefits

- Quickly adapts to site requirements
- Simplifies level, grade and vertical alignment setups
- Reduces time to do steep slope work and drainage installation
- Increases reliability, accuracy and durability
- Economize operating costs



GL612/GL622 – Maximum Versatility for Leveling, Grading and Vertical Alignment

GL612/GL622 Specifications

- Leveling accuracy^{1,3}: ± 0.5 mm/10 m, 1/16" @ 100 ft, 10 arc seconds
- Grade accuracy^{1,3}: ± 1.0 mm/10 m, 1/8" @ 100 ft, 20 arc seconds
- Operating diameter^{1,2}: appr. 800 m (2600 feet) with detector
- Grade range (Y, X-GL622): $\pm 25\%$ both axes (not simultaneously)
- Rotation: GL612: 300, 600, 900 rpm / GL622: 0 to 900 rpm
- Scan mode: 5 preset sizes + variable adjustment (GL622)
- Laser type: red diode laser 650 nm
- Laser class: GL612 Class 2, <3.2 mW / GL622 Class 3A/3R, <5mW
- Self-leveling range: appr. $\pm 14^\circ$
- Leveling indicators: LCD indications and LED flashes
- Radio range (HL750): up to 80 m (260 ft):
- Power source: NiMH battery pack
- Battery life¹: 35 hours NiMH; 40 hours alkaline
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Storage temp.: -20°C to 70°C (-4°F to 158°F)
- Tripod attachments: 5/8 x 11 horizontally and vertically
- Dust and waterproof: Yes - IP67
- Weight: 3.1 kg (6.8 lbs)
- Low voltage indication: LCD battery indicator
- Low voltage disconnection: unit shuts off
- Warranty: 5 Years

HL750 Laserometer

- Highly versatile receiver for basic and advanced leveling and aligning applications
- Works with GL612/GL622 in automatic Axis Alignment (only GL622), Grade Match and PlaneLok applications
- Key Features:
 - Digital readout of elevation
 - Exact distance from grade displayed
 - Anti-strobe sensor to prevent false reading from jobsite strobe lights
 - Large reception height to ease beam reception
 - Withstands a drop of up to 3m (10ft)
 - Radio communication - works with another HL750 for long range wireless remote display and monitoring capability
- User Benefits:
 - No need to go "on-grade" to measure;
 - Saves considerable time
 - Reduces rework by allowing remote monitoring
 - Increases reliability, accuracy and durability

RC602 Remote Control Specifications

- Operating range^{1,3}: up to 100 m (330 ft)
- Power source: 2 x 1.5V AA alkaline batteries
- Battery life¹: 130 hours
- Dust and waterproof: Yes - IP66
- Weight: 0.26 kg (0.57 lbs)

HL750 Laserometer Specifications

- Digital readout units: mm, cm, ft, in, frac. in
- Reception height: 127 mm (5 inches)
- Six On-grade sensitivities:
 - Ultra Fine 0.5 mm (~1/32 in)
 - Super Fine 1 mm (~1/16 in)
 - Fine 2 mm (~1/8 in)
 - Medium 5 mm (~1/4 in)
 - Coarse 10 mm (~1/2 in)
 - Calibration Mode 0.1 mm (~1/64 in)
- Battery life (2 x AA): 60+ hours continuous operation
- Auto shut-off: 30 minutes/24 hours
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Dust and waterproof: Yes - IP67
- Weight: 0.27 kg (9.5 oz)
- Warranty: 3 Years "No Excuses"

⁽¹⁾ at 21° Celsius (70° F)

⁽²⁾ under optimal atmospheric circumstances

⁽³⁾ along the axis



RC602 Radio Remote Control for all applications



HL750 Laserometer to measure and display beam location

Contact Information:

NORTH AMERICA

Trimble Spectra Precision Division
8261 State Route 235 • Dayton, Ohio 45424 • USA
Toll Free +1-888-272-2433 • Fax +1-937-482-0030
www.spectra-productivity.com

EUROPE

Trimble Kaiserslautern GmbH
Am Sportplatz 5 • 67661 Kaiserslautern • Germany
Phone +49-6301-711414 • Fax +49-6301-32213



To locate your nearest distributor, visit: <http://www.spectra-productivity.com/dealers/locator.html> or <http://dealerlocator.trimble.com/>
Specifications and descriptions are subject to change without notice. Please visit www.spectra-productivity.com or www.trimble.com/spectra for the latest product information.

© 2012, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo and Spectra Precision are trademarks of Trimble Navigation Limited, registered in the United States Patent and Trademark office and in other countries. All other trademarks are the property of their respective owners. PN 022507-288 (07/12)

SCAN THIS
CODE FOR MORE
INFORMATION

